MULTI-TENANT WATCHMAN® Virtual Security Guard Your

model

Can integrate with **CellGate external** cameras

ADVANCED TELEPHONE ENTRY with LIVE STREAMING VIDEO



WXL Surface Mount Can integrate w/CellGate external cameras

Surface Mount AA1XLSM ATT AA1XLSM VZN

AA1XLSM INT Flush Mount Kits[†] ENC-WFM1003 ENC-WFM1005

ENC-WFM1004 ENC-WFM1006



CELLGATE EXCLUSIVES

- Streaming cellular video telephone entry
- Integrates with up to 3 external cameras
- Voice Mail Intelligence VMI System ignores voice mail and continues call group
- Verizon or AT&T LTE service (No VolP fees required)
- Ships with both AT&T & Verizon SIM cards
- Prop open notification if gate is left open more than 3 minutes

NEW WXL FEATURES



OR CODE VISITOR MANAGEMENT



SMART SCREEN))((CALL MANAGEMENT

M Add up to 2 additional Weigand expansion ports per device Parts required

Mounting plate (supports up to two expansion boards) p/n: CB-WIM 4000 Expansion board (order one or two as required) p/n: CB-WIM 2000

-)))((**QR Code Visitor Management** Visitors can receive QR code invites with restricted date/time access on their smart phones.
 - **Smart Screen Call Management** Customizable touch screen call options, for improved visitor management.

ACCESS GUEST GR.CODE

WXL Pedestal Mount Can integrate w/CellGate external cameras

> Pedestal Mount AA1XLPE ATT AA1XLPE VZN AA1XLPE INT

ADDITIONAL FEATURES

- Brilliant 11" color touchscreen
- Built-in HID card reader
- 1 native 26-bit Wiegand expansion port
- Built-in postal lock
- Up to 3,000 directory listings
- Calls up to 6 app video contacts and 3 voice-only numbers per directory listing
- 30,000 local codes and 64,000 non-local codes

powered by:

) ((cellgate

😂 AT&T verizon



1.855.MY.GATES

cell-gate.com





*See external camera sheet for more details

• Up to 3 external cameras

Cloud-stored still photos

Recorded Video

Photos

External Camera Options

• Taken on entry transactions and on demand

or accessible via CellGate technical support

Pixel activated video stored on SD card

• Recording w/6-second pre-record

- Dedicated team for multi-tenant property management support
- Included with your service subscription at no charge
- Both personalized and video training
- TrueCloud[™] portal and CellGate app support
- Ongoing support for the life of your account

Tenant Benefits

- See live video of visitors on telephone entry
- QR code visitor management
- Easy to use CellGate iOS/Android app
- Tenant managed call groups
- Peace of mind and convenience

Web Portal **TrueCloud**¹⁰⁷

Manage All Your CellGate Devices on One Dashboard

- Master login for multiple properties
- Login privileges with multiple user tiers
- Call aroup management
- Resident and visitor credential management
- Mass credential management
- Setup and management of notifications, gate hold open schedules
- Date/time logs of all gate and door access attempts, access codes used, and photos of each gate access attempt (with Advantage and Advantage Plus plans)
- Hosted by Microsoft Azure

App Available at Store and Google Play

1.855.MY.GATES

CellGate App))((

- Receive video/audio calls from visitors Property Manager Can:
- Manage Resident app functions:
- Allow residents to issue visitor QR codes
- Allow residents to manage call groups
- Open or hold open from anywhere
- Close on demand (override holds)
- Take photos from internal and external cameras



model

Can integrate with **CellGate external** cameras

SPECIFICATIONS

External Camera Options Bullet Cameras

4mm Fixed Focal Lens 5-64mm Varifocal Lens 2.8-12mm Varifocal Lens Dome Camera 3-10.5mm Varifocal Lens

HD Camera angles: Horizontal: 120° Vertical: 64° Camera MP: 3MP

Power Consumption Hardware: 625mA (average) External Cam: 350ma to 1A

1 - Wiegand Expansion Port (26 bit) Add up to 2 additional Weigand expansion ports per device Parts Required; Mounting plate (supports up to two expansion boards) p/n: CB-WIM 4000 Expansion board (order one or two as required) p/n: CB-WIM 2000

3 Relays: Switching voltage: 30v Switching current: 5A

3 Digital inputs

ARRAN

IP65 - outdoor rated

Operating Temperature -20°C - 55°C

Dimensions - Surface Mount Height- 375mm (14.75") Width- 305mm (12.75") Depth- 95mm (3.75")

Dimensions - Pedestal Mount Height - 375mm (14.75") Width- 305mm (12.75") Depth- 95mm (3.75") - Bottom 152mm (6") - Top All electronics are mounted inside, no external box/wiring needed.

Cellular Technology/Networks LTE: AT&T and Verizon

Internet Shipped with DHCP default Private IP addresses may be required.

Included in box Watchman WXL Power supply – 5A Magnetic switch Installation manual & user manual

Flush Mount Kits (Surface Mount Model): ENC-WFM1003 includes trim ring and rough-in box ENC-WFM1004 includes trim ring (no rough-in box) ENC-WFM1005 includes trim ring, L-bracket antennas, rough-in box ENC-WFM1006 includes trim ring, L-bracket antennas (no rough-in box)

Antenna Options L-bracket

Signal booster



cell-gate.com

